

Presenting,

EECO CARE ADD COMFORT TO CARE.



*Images for illustration purposes only






TECHNICAL SPECIFICATIONS

VARIANT		AMBULANCE	AMBULANCE SHELL*
DIMENSION AND WEIGHT			
Kerb Weight (Kg)		1030	940
Full Length (mm)		3675	3675
Full Width (mm)		1475	1475
Full Height (mm) Unladen (excluding top light)		1930	1930
Seating Capacity		3+1 (Patient)	3 (with recommended seating capacity of 3 person + 1 patient after fabrication)
Tread	Front (mm)	1280	1280
	Rear (mm)	1290	1290
Wheelbase (mm)		2350	2350
Min. Turning Radius (m)		4.5	4.5
ENGINE (PETROL)			
Engine Type		K12N	K12N
Engine Displacement (cc)		1197	1197
Max. Output (kW/rpm)	Petrol	59.4/6000	59.4/6000
Max. Torque (Nm/rpm)	Petrol	104.4/3000	104.4/3000
Tank Capacity	Petrol (L)	32	32
TRANSMISSION			
Petrol		5MT	5MT
BRAKE/CHASSIS			
Brake Front		Disc	Disc
Brake Rear		Drum	Drum
Front Suspension		MacPherson Strut	MacPherson Strut
Tyre Size		155R13C 8PR	


FEATURES

VARIANT	AMBULANCE	AMBULANCE SHELL*
COMFORT		
Air Conditioner	√	√
Heater	√	√
Sliding Driver Seat	√	√
Head Rest-Front Row	Integrated	Integrated
INSTRUMENT PANEL & CONSOLE	ÿ	ů
Illuminated Hazard Switch	√	√
Digital Display in Instrument Cluster	√	√
12 Volt Accessory Socket	✓	√
Multi Tripmeter	√	√
Digital Speedometer	· √	√
Dome Lamp Battery Saver Function	· √	·
INTERIOR	·	·
Both Side Sunvisor	√	√
Assist Grip (Co-Driver + Rear)	√	√
Molded Roof Lining	√	√
Molded Floor Carpet	√ √	√ √
Interior Color (Dual Tone)	√	√ √
	√ √	√
Front Cabin Lamp Cabin Air Filter	√ √	√ √
Steering Lock	√ √	√ √
	٧	√
EXTERIOR		
Wheel Cover	Center Cap	Center Cap
Front Mud Flaps	√	√
Outside Rear View Mirror (Left & Right)	√	√
Ambulance Decal - Front & Rear	√	√
Partly Frosted Rear side windows	√	√
Partly Frosted Back Door windows	√	√
SAFETY & SECURITY		
Immobilizer	√	√
Headlamp Leveling	√	√
Side Impact Beams	√	√
Offset Crash Compliance (as per AIS 098)**	√	√
Seat Belts for all Seats	√	√
High Mount Stop Lamp	√	√
Reverse Parking Sensor System	√	√
Seat Belt Reminder (Dr + Co-Dr)	√	√
ABS with EBD	√	√
Dual Airbag	✓	√
FACILITIES ON BOARD		
Revolving Roof Lamp	√	√
Molded Rubber Matting in Rear Cabin	√	√
Siren	√	√
Public Address System (Amplifier, Mike and Speaker)	√	√
Two LED lights inside Rear Cabin for Illuminated	√	√
Stretcher Assembly (Monoblock Stretcher)	· √	- · · · · · · · · · · · · · · · · · · ·
Attendant's Seat	· √	√
Space for First Aid and Nursing Kit	→	√
Oxygen Cylinder Clamp	√	-
Hook for Infusion Mounting	√	√
TOOK OF THIS SECTION THOUSAND	•	•









nce, with recommended seating capacity of 3 Persons + 1 Patient.

art 1 requirements except related to Stretcher and Oxygen cylinder mounting provision.

t exceed 1030 kg.

equipment specifications, and models of ambulance/ambulance shell and also to discontinue models and/or replace any part or accessory with any product. Accessory
ffer according to the variant and model. Any offers made will be subject to availability of the product. Images are for illustration purposes only. Actual vehicle body color
ling air bag, kindly refer to the Owner's Manual. **Crash Compliance is with Offset Crash (as per AlS 098).